



# PRIVACY & DECORATIVE FILM

## Vermont – Frosted 4mm Stripes on Clear

DE-VERM-ISR

Opalux® Vermont patterned film gives architects, designers and specifiers fresh scope for decorating and enhancing glass in partitioning and interior projects in all types of office, commercial, retail and residential buildings.

The Vermont patterned film is typically used in glazed screens in reception areas, lobbies, corridors, internal office partitions and other areas where a degree of privacy is required and a light, open atmosphere is desirable. Applying Opalux® decorative films gives you the option to remove, replace or update designs in the future, if required. As well as adding a distinctive designer style to your office interior, this product allows some modesty for reception areas and meeting rooms, where total screening is not required. The Opalux Vermont is a decorative patterned film for aesthetic and functional enhancement of the glass.

### FEATURES

- High light transmission
- Quick, retro-fit installation
- Removable
- Incorporate with manifestations and graphics

### BENEFITS

- Gives the glass a decorative appearance whilst maintaining abundant light levels
- Introduce privacy when and where it is required; ideal for glazing in rooms with a change of use
- Gives the option to remove, replace or update in the future
- Can be used to help satisfy Health & Safety requirements for large areas of uninterrupted glazing, such as glass partitions

| PERFORMANCE DATA                      |                      | DE-VERM-ISR |
|---------------------------------------|----------------------|-------------|
| SOLAR ENERGY                          | Transmitted          | 69%         |
|                                       | Reflected            | 19%         |
|                                       | Absorbed             | 12%         |
| VISIBLE LIGHT                         | Transmitted          | 71%         |
|                                       | Reflected (Interior) | 18%         |
|                                       | Reflected (Exterior) | 14%         |
| UV Rejection                          |                      | 99%         |
| Glare Reduction                       |                      | 19%         |
| Shading Coefficient                   |                      | 0.83        |
| Solar Heat Gain Coefficient (G-Value) |                      | 0.72        |
| U-Value (W/m²K)                       |                      | 5.62        |
| Total Solar Energy Rejected           |                      | 28%         |
| Product Warranty                      |                      | 7 years     |

| PHYSICAL PROPERTIES                   |                     |
|---------------------------------------|---------------------|
| Material                              | PET                 |
| Liner                                 | Silicone Coated PET |
| Structure                             | Single Ply          |
| Adhesive Type                         | Acrylic             |
| Suitable for plotter-cutting graphics | No                  |

### NOTES

Test results are produced from film applied to 3mm clear single glass. Performance data is subject to change without prior notice. Accurate selection of window film requires specialist knowledge, and it is recommended that specifiers contact the company at the specification stage. Please refer to the Opalux® Product Warranty Form for the full terms of the Opalux® limited warranty. It is the users' responsibility to ensure the product is suitable for the intended use. The seller shall not be liable for any direct, indirect or consequential loss or damage howsoever arising.

### SPECIFICATION

The privacy window film is to be Opalux® Vermont, as manufactured by Opalux® ([www.opaluxwindowfilms.com](http://www.opaluxwindowfilms.com)). The film is to be installed to the interior surface of the glass, and the unique product roll numbers used are to be registered in accordance with the manufacturer's warranty procedure.