

SAFETY & SECURITY FILM

100 Micron – Reflective Silver 35

SA-35RS/100-iSR



Opalux® 100-micron Reflective Silver 35 combines the benefits of solar heat and glare control with safety and security in the one film installation.

Opalux® single ply combined silver 35 is used as a minimum specification for safety film and can be used by organisations to address regulation 14 of the workplace (Health, Safety & Welfare) regulation 1992 by upgrading low-level glazing where necessary for reason of health and safety, along with the features of a solar control film. It is designed to make glass safer, both by strengthening it against breakage and helping hold dangerous shards of shattered glass in situations where breakage does occur. They are suitable for use in applications in the workplace and home. Other benefits can include improved security by creating a deterrent to “smash-and-grab” and forced entry crime, and providing protection against the vandalism of glass through graffiti such as the etching or scratching of glass. Also the combined daytime reflective appearance offers extra privacy protection and good heat and glare rejection.

FEATURES

- Good solar heat and glare rejection
- Cuts energy use for cooling
- Reflective daytime appearance
- Quick, retro-fit installation
- Scratch-resistant coating
- Screening of harmful UV rays

BENEFITS

- Alleviate the discomfort caused by excessive heat and glare
- Provides the option for solar control still to be provided where an internal installation is deemed not possible or not advisable
- Increased daytime privacy from outside looking in
- Can be used where costly and disruptive large-scale replacement of existing glazing is not a viable option
- Suitable for most non-abrasive window-cleaning methods
- Reduced fading of interior furnishings

PERFORMANCE DATA		SA-35RS/100-iSR
SOLAR ENERGY	Transmitted	21%
	Reflected	42%
	Absorbed	37%
VISIBLE LIGHT	Transmitted	34%
	Reflected (Interior)	26%
	Reflected (Exterior)	28%
UV Rejection		99%
Glare Reduction		61%
Shading Coefficient		0.40
Solar Heat Gain Coefficient (G-Value)		0.35
U-Value (W/m²K)		5.51
Total Solar Energy Rejected		65%
Product Warranty		10 years

PHYSICAL PROPERTIES	
Description	Medium Tint
Film Thickness	100-Microns (4-thou)
Structure	Multi Ply Laminate
Tensile Strength	25,000 PSI
Break Strength	100 Pounds per Inch (width)
Adhesive Type	Acrylic Pressure Sensitive
Peel Strength	6 to 7 Pounds per Inch

NOTES

Test results are produced from film applied to 3mm clear single glass. Performance data is subject to change without prior notice. It is the users' responsibility to ensure the product is suitable for the intended use. The seller shall not be liable for any direct, indirect or consequential loss or damage howsoever arising.

SPECIFICATION

The safety and security window film is to be Opalux® SA-35RS/100-iSR, as manufactured by Opalux® (www.opaluxwindowfilms.com). The film is to be installed to the interior surface of the glass, and the unique product roll numbers used are to be registered in accordance with the manufacturer's warranty procedure.