



# TPWF-40CL -Clear Temporary Protection Film

TPWF-40CL is a self wound polyethylene film with an acrylic adhesive and has been designed to protect sensitive surfaces against dirt and damage during processing, storage and mounting.

## **TECHNICAL INFORMATION:**

Film Backing:	Polyethylene LDPE
Colour:	Clear (Neutral/Transparent)
Adhesive Type:	Acrylic
Film Thickness:	40micron
Peel Adhesion to Stainless Steel:	60+/- 10c N/cm
Nominal MD Elongation:	280%
Nominal TD Elongation:	550%
Roll size:	1200mm x 100m

## Guideline application instructions for TPWF-40CL

1. For a good application, surface must be free from fat, oils, solvents, dust and/or other extraneous substances
2. The film must be used without folds or bubbles and without excessive tension
3. Application temperature: T.A.(+10°C<+40°C)

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. The supplier assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.